



VI AUSSTECKTRANSPARENTE

Model	VI-SO5-A-160x160	VI-SO-5-A-192x192	VI-SO-8-A-128x96	VI-SO-8-A-128x128
LED Typ	SMD	SMD	SMD	SMD
Auflösung(px)	160 x 160	192 x 192	128 x 96	128 x128
max. Helligkeit cd/m ²	>6000	>6000	>6000	>6000
Farbtemperatur	5000 - 9500 K	5000 - 9500 K	5000 - 9500 K	5000 - 9500 K
idealer Betrachtungsab- stand	5m - 35 m	5m - 45 m	8m - 40 m	8m - 50m
Eingangsspannung	220 VAC	220 VAC	220 VAC	220 VAC
Leistungsaufnahme typ.	389 Watt	560 Watt	373 Watt	498 Watt
Leistungsaufnahme max	1750 Watt	2520Watt	1680 Watt	2240 Watt
Maße (BxHxT) (mm ³)	800 x 800 x 180	960 x 960 x 180	1024 x 768 x 180	1024 x 1024 x 180
Gewicht	28 Kg	39 Kg	34 Kg	44 Kg
IP Klasse (vorne/ seite)	IP65 / IP54	IP65 / IP54	IP65 / IP54	IP65 / IP54
Steuerung	Asynchron, 4 Gbyte ROM, 512 MB RAM, 100M Ethernet, USB			
Unterstützte Medienfor- mate	Bilder: .bmp; .jpg; .jpeg Video: .giv; .swf; .avi; .3GP; .asf; .avm; .avs; .dat; .flv; .mkv; .mov; .mp4; .mpeg; .mpg; .nsv; .wmv			

