



VI -PYLON



Model	VI-SI-5-P-160x352	VI-SI-8-P-128x224	VI-DI-8-P-128x224
LED Typ	SMD	SMD	DIP
Auflösung	160 x 352 px	128 x 224 px	128 x 224 px
max. Helligkeit	>6000 cd/m ²	>6000 cd/m ²	>8000 cd/m ²
Farbtemperatur	5000 - 9500 K	5000 - 9500 K	5000 - 9500 K
idealer Betrachtungsabstand	5m - 75m	8m - 90m	8m - 90m
Eigangsspannung	220 VAC	220 VAC	220 VAC
Leistungsaufnahme typ.	578 Watt	490 Watt	388 Watt
Leistungsaufnahme max.	2310 Watt	1960 Watt	1550 Watt
Maße (BxHxT)	960 x 1760 x 80	1024 x 1792 x 80	1024 x 1792 x 80
Gewicht	45 Kg	55 Kg	55 Kg
IP Klasse (vorne/ seite)	IP40 / IP20	IP40 / IP20	IP40 / IP20
Steuerung	Asynchron, 4 Gbyte ROM, 512 MB RAM, 100M Ethernet, USB		
Unterstützte Medio enfor- mate	Bilder: .bmp; .jpg; .jpegVideo: .giv; .swf; .avi; .3GP; .asf; .avm; .avs; .dat; .flv; .mkv; .mov; .mp4; .mpeg; .mpg; .nsv; .wmv		

